



FW60

Semi-commercial washer

FD112-FDC112-FDHP112

Semi-commercial dryer

INDUSTRIAL
BY DESIGN



COMPACT
DESIGN



STACKABLE
UNIT



LOW ENERGY
CONSUMPTION

Features

WASHER EXTRACTORS

- White cabinet
- Stainless steel drum and tub
- Easy to use timer
- Mop and medical programmes
- Soap hopper at the front
- Matching dryer available – space saving when placed on top

DRYERS

- White cabinet
- Stainless steel drum and tub
- Large door opening (Ø45 cm)

Options

WASHER EXTRACTORS

- External coin meter
- Drain valve
- Liquid soap pumps
- Marine voltages available

DRYERS

- External coin meter
- Condens unit (FDC112)
- Marine voltages available
- Heat pump heating (FDHP112)

FW60

FD112 - FDC112 - FDHP112

TYPE		FW60
CAPACITY		
drum capacity	kg	6
drum volume	l	60
drum diameter	mm	Ø 480
DRUM SPEED		
extraction speed	rpm	1600
G-factor		690
HEATING		
electrical	kW	3,2
CONNECTIONS		
electrical		200V/50-60Hz/1 230V/50-60Hz/1 400-415V/50-60Hz/3+N 400-440V/60Hz/3
water	inch	3/4"
CIRCUIT BREAKER		230V-10A / 400V-16A
DRAIN		
		pump standard, drain valve optional
DIMENSIONS		
size H x W x D	mm	850 x 595 x 585
TRANSPORT DATA		
gross	kg	78
net	kg	76
volume (packed)	m ³	0,53
packed H x W x D	mm	920 x 640 x 660

TYPE		FD 112	FDC 112	FDHP 112
		vented dryer	condense dryer	heat-pump dryer
CAPACITY				
drum capacity	kg	6	6	6
drum volume	l	112	112	112
drum diameter	mm	Ø 571	Ø 571	Ø 571
HEATING				
electrical	kW	3	2,5	-
CONNECTIONS				
electrical		200V/50-60Hz/1 230V/50-60Hz/1 400-415V/50-60Hz/3+N 400-440V/60Hz/3	200V/50-60Hz/1 230V/50-60Hz/1 400-415V/50-60Hz/3+N 400-440V/60Hz/3	200V/50-60Hz/1 230V/50-60Hz/1 400-415V/50-60Hz/3+N 400-440V/60Hz/3
CIRCUIT BREAKER		230V-10A / 400V-16A	230V-10A / 400V-16A	230V-10A / 400V-16A
AIRFLOW	m ³ /h	123	123	123
AIR EVACUATION	mm	100	-	-
DIMENSIONS				
size H x W x D	mm	850 x 595 x 585	850 x 595 x 585	850 x 595 x 585
TRANSPORT DATA				
gross	kg	42	46	54
net	kg	40	44	52
volume (packed)	m ³	0,53	-	-
packed H x W x D	mm	920 x 640 x 660	920 x 640 x 660	920 x 640 x 660