



CD10

Dryer for semi-commercial
laundry applications

INDUSTRIAL
BY DESIGN

Features

- Galvanized steel cylinder
- Top, front and side panels standard available in white
- Door opens 180° for easy loading and unloading
- Oversized lint filter located in front for easy cleaning
- Noiseless exhaust blower assures short drying times and low operating costs
- 5 drying programs

Options

- Top, front and side panels in stainless steel
- Coin-operated version for vended laundry applications



OPTIONAL

CD10

| TYPE | | CD10 |
|-------------------------|--|--|
| CAPACITY | | |
| drum volume | l | 201 |
| MOTOR | | |
| power motor | kW | 0,25 |
| AIR OUTLET | | |
| diameter | mm | 102 |
| HEATING | | |
| electric | kW | 5,35 |
| CONNECTIONS | | |
| gas inlet connection | mm | 9,5 |
| gas consumption | BTU/hr | 25.000 |
| electrical requirements | E - 120/240/60/1-30A - 120/280/60/1-30A - 220/60/1-30A - 230/50/1-30A - 400/50/3-15A G - 120/60/1-15A - 220/60/1-10A - 230/50/1-10A | |
| DIMENSIONS | | |
| size H×W×D | mm | OPL: 1027 x 683 x 711 - Vend: 1126 x 683 x 711 |
| TRANSPORT DATA | | |
| gross weight | kg | OPL: E - 70 / G - 73 - Vend: E - 73 / G - 75 |
| net weight | kg | OPL: E - 66 / G - 68 - Vend: E - 68 / G - 70 |
| packed H×W×D | mm | 1156 x 737 x 832 |
| packed volume | m ³ | 0,71 |

